FENCE STRIPS cover and privacy

CATALOGUE





WE SPECIALIZE IN EXTRUSION OF PLASTIC PROFILES

- Thermoplast has over 30 years of experience in designing and building tools for extrusion, co-extrusion and post-extrusion of custom technical profiles for clients from various industries.
- Thermoplast® is a leader among manufacturers and suppliers of original fence tapes systems on the Polish market, including fencing strips made of the highest quality polypropylene.
- We offer a wide range of standard profiles for various industries, including: furniture, refrigeration, ventilation, air-conditioning, fencing and agricultural, garden architecture, construction, sales support. We also implement individual projects, even most complex technical profiles in terms of shape, material and conditions of use.
- We offer the widest range of original fencing strips and covers for standard 2D and 3D panels as well as fencing meshes and balcony railings on the Polish market. The offer varies both in terms of the method of mounting, structure of the strips, their width and color, which makes it possible to create functional, aesthetic, individually designed fences.

THERMOPLAST® KEY PRODUCT GROUPS










EXCELLENT COVER FOR YEARS

CONTENTS

ADVANTAGES OF USING STRIPS	
HORIZONTAL MOUNTING SYSTEM	05
APPLICATION AND BENEFITS	
FENCE STRIPS - CLASSIC LINE	
FENCE STRIPS - SMART MATT	
FENCE STRIPS - ORANGE SKIN	10
FENCE STRIPS - BASIC	
FENCE STRIPS - LARGE TECHNORATTAN	
VERTICAL MOUNTING SYSTEM	
FENCE STRIPS - SIMPLE LINE	
FENCE COVERS - THE GUARD	
CUSTOM MADE COLORS	17









FENCE STRIPS THERMOPLAST®

ORIGINAL FENCE COVERS

MADE IN UE

protection and privacy on properties, terraces and balconies

Thermoplast® fencing covers are an innovative solution that allows to create modern, aesthetic and functional fencing fillings for people who want to maintain privacy on the property, in the garden

or on the balcony. They are perfect for fencing panels, mesh fencing and balustrades of balconies.

ADVANTAGES OF USING THERMOPLAST® COVERS

- - UV resistant, do not discolour in the sun
- remain soft and flexible when bent
- frost-resistant, unbreakable in low temperatures
- do not deform in high temperatures
- provide an aesthetic appearance on both sides of a fence panel

- do not require maintenance and impregnants
- easy and quick assembly without the use of specialized tools
- variety of applications (panels, balcony railings, mesh panels)
- protection against wind and adverse weather conditions.
- modern design and various widths



HORIZONTAL MOUNTING

Thermoplast® fence strips

perfect for filling panels, mesh fences and balcony railings, providing an aesthetic and durable cover. We offer them in a wide range of colors and patterns and in various widths.



VERTICAL MOUNTING

Simple Line System

a functional and aesthetic polypropylene cover for 2D and 3D fencing panels. A set consists of 60 meters of fencing tape and 100 assembly clips. We offer Simply Line in several widths, patterns and colors.



The Guard System

a set of plastic slats that is matched to 3D fence panels. The Guard is available in several sizes, so it can be used in the most popular heights of 3D panels.



THERMOPLAST® ORIGINAL FENCE COVERS ARE A GUARANTEE OF THE HIGHEST QUALITY PRODUCTS

All production processes in Thermoplast® are certified in accordance with ISO 9001, and the quality is controlled by specialists throughout production process.







IDEAL SOLUTION FOR-











TECHNICAL DATA

Material	Polypropylene (PP)
Darkening	≈100%
Application	fencing panels, mesh fences, balcony railings
Weight	~552 gramm/m², ~630 gramm/m², 789 gramm/m²
Assembly	assembly without the use of specialized tools
Assembly	horizontal mounting



MODERN DESIGN







SMART MATT



ORANGE SKIN



BASIC



TECHNORATTAN LARGE

AVAILABLE WIDTHS



190 mm	
1 box	26 m
1 m²	5 lm
1 box	5 m ²



95 mm	
1 box	52 m
1 m²	10 lm
1 hox	5 m ²



47,5 mm	
1 box	50 m
1 m²	20 lm
1 box	2,5 m ²

MOUNTING CLIPS FOR FENCE STRIPS



UNIVERSAL CLIP AP 828

End profile with strong handle suitable for each wire thickness in a panel.



STANDARD CLIP AP 785

End profile for panels with wires with a cross-section 4 - 6 mm.



OMEGA CLI AP 888

End profile for panels with wires with a cross-section 3,5 - 5,5mm.



The use of best quality plastic - **Polypropylene**, guarantees the highest UV resistance, durability and flexibility of fencing strips.



MADE IN EU



INNOVATIVE SOLUTION



HIGHEST QUALITY



FAST AND EASY ASSEMBLY

HORIZONTAL MOUNTING

How in a quick and easy way turn a garden, terrace or balcony into a private space?



Waive the fence tape onto the panel.



Fasten the tape in the end clip.



Attach the end clip with the fence strip to the panel.

CALCULATION

FENCE STRIPS 190 n	nm		PANE	EL SIZE [M	х м]					
	2,5 X 1,2 2,5 X 1,4 2,5 X 1,6 2,5 X 1,8 2,5 X 2,0									
	1	1	1	1	1	1				
	2	2	2	2	2	2				
	3	2	3	3	3	3				
	4	3	3	4	4	4				
ν	5	3	4	4	5	5				
NUMBER OF PALLETS	6	4	5	5	6	6				
PA	7	5	5	6	7	7				
ㅂ	8	5	6	7	8	8				
ä	9	6	7	8	9	9				
Ξ	10	6	7	8	9	10				
Ž	15	9	11	12	14	15				
	20	12	14	16	18	20				
	30	18	21	24	27	30				
	40	24	28	32	36	40				
	50	30	35	40	45	50				
		box 19	0 mm x 2	26 lm - [5	m21					

FENCE STRIPS 95 m	5	PANEL SIZE [M X M]						
	2,5 X 1,2 2,5 X 1,4 2,5 X 1,6 2,5 X 1,8 2,5 X 2,0							
	1	1	1	1	1	1		
	2	2	2	2	2	2		
	3	2	3	3	3	3		
	4	3	3	4	4	4		
δ	5	3	4	4	5	5		
NUMBER OF PALLETS	6	4	5	5	6	6		
PA	7	5	5	6	7	7		
ㅂ	8	5	6	7	8	8		
떒	9	6	7	8	9	9		
Ĕ	10	6	7	8	9	10		
ž	15	9	11	12	14	15		
	20	12	14	16	18	20		
	30	18	21	24	27	30		
	40	24	28	32	36	40		
	50	30	35	40	45	50		
		box 95	5 mm x 5	2 lm - [5	m²]			

FENCE									
STRIPS 47,5 n	nm	PANEL SIZE [M X M]							
		2,5 X 1,2 2,5 X 1,4 2,5 X 1,6 2,5 X 1,8 2,5 X 2,0							
	1	2	2	2	2	2			
	2	3	3	4	4	4			
	3	4	5	5	6	6			
	4	5	6	7	8	8			
δ	5	6	7	8	9	10			
NUMBER OF PALLETS	6	8	9	10	11	12			
PAI	7	9	10	12	13	14			
A	8	10	12	13	15	16			
떒	9	11	13	15	17	18			
Ξ	10	12	14	16	18	20			
Ž	15	18	21	24	27	30			
	20	24	28	32	36	40			
	30	36	42	48	54	60			
	40	48	56	64	72	80			
	50	60	70	80	90	100			
		box 47 ,	5 mm x 5	0 lm - [2	,5m²]				



CLASSIC LINE

















MADE IN POLAND

MADE OF BEST QUALITY POLYPROPYLENE

TO WEATHER CONDITIONS

RESISTANT TO RADIATION, COLOR DURABILITY

WARRANTY

AVAILABLE WIDTHS:







190 mm

95 mm

47,5 mm


CLASSIC LINE FENCE STRIP												
PROFILE NAME	FILE NAME WIDTH THICKNESS WEIGHT PACKAGE				INDEX							
				ROLL	26 lm	701P.XXXXK0026.190.P						
701	100 mm	190 mm 1,65 mm 750-770 gramm/m² STRIPS	750 770 202 202 /22		10 x 2,55 m	701P.XXXXK2550.190.P						
701	190111111		1,0511111	1,05 11111	1,05 mm /50-770 gramm/m		1,05 mm 750-770 gramm/m		/50-//0 gramm/m-	750-770 grammini	10 x 2,53 m	701P.XXXXK2530.190.P
					10 x 2, 52 m	701P.XXXXK2520.190.P						
706	95 mm	1,65 mm	750-770 gramm/m²	ROLL	2 x 26 lm	706P.XXXXK0026.95.X2						
685	47,5 mm	1,3 mm	750-770 gramm/m²	ROLL	50 lm	685P.XXXX.K0050.47.X2						

CLASSIC LINE - AVAILABLE RANGE OF COLORS



TH 520 (RAL 6005)









TH 909 (RAL 7040)

TH 947 (RAL 7030)

TH 945 (RAL 7016)



TH 329 (RAL 9003)

Other colors of the tapes are made to order.
Colors presented in the catalog may slightly differ from the actual colors.



SMART MATT







MADE IN POLAND



AFFORDABLE FOR EVERYONE



BEST QUALITY POLYPROPYLENE



TO WEATHER CONDITIONS



RESISTANT TO RADIATION, COLOR DURABILITY



TION, WARRAI

AVAILABLE WIDTHS:




190 mm

SMART MATT FENCE STRIP							
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	PACKAGE		INDEX	
K11	190 mm	1,1 mm	770-790 gramm/m²	ROLL	26 lm	K11.XXXXK0026.190.BL	

SMART MATT - AVAILABLE RANGE OF COLORS



TH 520 (RAL 6005)



TH 909 (RAL 7040)



TH 945 (RAL 7016)



As usual, modern design, uncompromising quality and a surprisingly favorable price!



Other colors of the tapes are made to order.
Colors presented in the catalog may slightly differ from the actual colors.



ORANGE SKIN













MADE OF BEST QUALITY POLYPROPYLENE



TO WEATHER CONDITIONS



RESISTANT TO RADIATION, COLOR DURABILITY



AVAILABLE WIDTHS:



ORANGE SKIN FENCE STRIP								
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	P	ACKAGE	INDEX		
K08	190 mm	0,85 mm	580-600 gramm/m ²	ROLL	26 lm	K08.XXXXK0026.190.0S		
1/12	100	120	F00 C00 are mm /m²	ROLL	26 lm	K12.XXXXK0026.190.05		
K12 190 r	190 111111	190 mm 1,20 mm	580-600 gramm/m ²	STRIPS	10 x 2,55 m	K12.XXXXK2550.190.0S		

ORANGE SKIN - AVAILABLE RANGE OF COLORS







TH 520 (RAL 6005) TH 909 (RAL 7040)

TH 945 (RAL 7016)



Other colors of the tapes are made to order. Colors presented in the catalog may slightly differ from the actual colors.



BASIC











AFFORDABLE FOR EVERYONE



BEST QUALITY
POLYPROPYLENE



TO WEATHER



RESISTANT TO RADIATION, COLOR DURABILITY



N, WARRAN

AVAILABLE WIDTHS: _



190 mm

BASIC FENCE STRIP								
PROFILE NAME	OFILE NAME WIDTH THICKNESS WEIGHT PACKAGE				INDEX			
		0 mm 0,65 mm	550-570 gramm/m²	ROLL	26 lm	K06.XXXXk0026.190.ST		
K06	100			550, 570 gramm/m²	PE SLEEVE	50 lm	K06.XXXXK0050.190.BS	
K06 190 mm	190 111111			PL JLLLVL	35 lm	K06.XXXXK0035.190.BS		
			SET	50 lm	K06.XXXXK0050.190.BS			

BASIC - AVAILABLE RANGE OF COLORS



TH 520 (RAL 6005)







TH 909 (RAL 7040)

TH 945 (RAL 7016)



Other colors of the tapes are made to order.

Colors presented in the catalog may slightly differ from the actual colors.



TH 329 (RAL 9003)

TECHNORATTAN LARGE













MADE OF BEST QUALITY POLYPROPYLENE



TO WEATHER CONDITIONS



RESISTANT TO RADIATION, COLOR DURABILITY



AVAILABLE WIDTHS:



190	mm	

TECHNORATTAN LARGE FENCE STRIP							
PROFILE NAME WIDTH THICKNESS WEIGHT PACKAGE INDEX							
				ROLL	26 lm	K20.XXXXK0026.190.RW	
K20	190 mm	2,0 mm	1210-1250 gramm/m²	ROLL	5,1 lm	K20.XXXXK5100.190.RW	
				STRIPS	10 x 2, 55 m	K17.XXXXXK2550.190.RW	

TECHNORATTAN LARGE - AVAILABLE RANGE OF COLORS







TH 520 (RAL 6005)

TH 909 (RAL 7040)

TH 945 (RAL 7016)



Other colors of the tapes are made to order. Colors presented in the catalog may slightly $\,$ differ from the actual colors.



SIMPLE LINE SYSTEM

















MADEIN

AFFORDABLE MADE OF BEST QUALITY POLYPROPYLENE

RESISTANT TO WEATHER CONDITIONS

RESISTANT TO RADIATION, COLOR DURABILITY

WARRANT

■ TECHNICAL DATA

Material	Polypropylene (PP)
Darkening	≈100%
Application	2D and 3D panels
Weight	550-570 gramm/m², 580-600 gramm/m²
Assembly	assembly without the use of specialized tools
Assembly	vertical assembly

PACKAGE

60 m of fence tape +100 end clips

SIMPLE LINE - BASIC SYSTEM							
PROFILE NAME WIDTH THICKNESS WEIGHT PACKAGE INDEX							
	44 mm			ROLL	60 lm	SP.K06.XXXXK060.44.BS	
SP.K06	48 mm	0.65	550-570 gramm/m²	ROLL	60 lm	SP.K06.XXXXK060.48.BS	
	50 mm	0,65 mm		ROLL	60 lm	SP.K06.XXXXK060.50.BS	
	55 mm			ROLL	60 lm	SP.K06.XXXXK060.55.BS	


SIMPLE LINE - ORANGE SKIN SYSTEM								
PROFILE NAME	PROFILE NAME WIDTH THICKNESS WEIGHT PACKAGE INDEX							
	44 mm			ROLL	60 lm	SP.K08.XXXXK060.44.0S		
SP.K08 48 mm 50 mm	48 mm	0,85 mm	580-600 gramm/m²	ROLL	60 lm	SP.K08.XXXXK060.48.0S		
	50 mm			ROLL	60 lm	SP.K08.XXXXK060.50.0S		
	55 mm			ROLL	60 lm	SP.K08.XXXXK060.55.0S		



MODERN DESIGN



COLORS



MOUNTING CLIPS




AVAILABLE WIDTHS






















FAST AND EASY ASSEMBLY




Cut the tape to appropriate length.



Fasten the tape together with a clip on the bottom wire panel.





Waive the tape vertically on the panel.




Fasten the tape together with a clip on the top panel wire

QUICK CALCULATION









THERMOPLAST® ORIGINAL FENCE COVERS

THE GUARD SYSTEM

















MADE IN POLAND

FOR EVERYONE BEST QUALITY
POLYVINYL CHLORIDE

TO WEATHER CONDITIONS

RESISTANT TO RADIATION, COLOR DURABILITY

WARRANTY

TECHNICAL DATA

Material	Polyvinyl chloride (PVC)
Darkening	≈100%
Application	2D and 3D fence panels
Grubość (ściany profilu głównego)	0,70 mm
Assembly	assembly without the use of specialized tools
Assembly	vertical assembly



It is not recommended to install **TheGuard** in very windy areas (safety considerations).

THE GUARD SYSTEM								
PROFILE NAME	SLAT WIDTH	SPACING BETWEEN PANEL WIRES	MAIN PROFILE WALL THICKNESS	PACKAGE	PANEL			
				SET	2,5 M X 1,03 M			
		50 mm		SET	2,5 M X 1,23 M			
THE CHARR	44 mm		0,70 mm	SET	2,5 M X 1,53 M			
THE GUARD				SET	2,5 M X 1,73 M			
				SET	2,5 M X 1,93 M			
				SET	2,5 M X 2,03 M			
				SET	2,5 M X 1,03 M			
	48mm	55 mm	0,70 mm	SET	2,5 M X 1,23 M			
THE CHARD				SET	2,5 M X 1,53 M			
THE GUARD				SET	2,5 M X 1,73 M			
				SET	2,5 M X 1,93 M			
				SET	2,5 M X 2,03 M			





THERMOPLAST® ORIGINAL FENCE COVERS

COLORS

TH 520 (RAL 6005) TH 945 (RAL 7016)

COMPATIBILITY






■ THE SET CONSISTS OF

Each **TheGuard** set contains all necessary elements to cover 1 panel.


THE GUARD SYSTEM								
MAIN SLATS	SIDE SLATS		HORIZONTAL SLAT FINISHING (two versions) TOP SLAT					

The set consists of:

- main slats for vertical mounting
- 2 side slats for vertical mounting
 (2 narrower slats to be mounted at both ends of the panel)
- horizontal slat mounted in the panel corrugation
- finishing top slat
- mounting clips mounted on the lower horizontal wire



FAST AND EASY ASSEMBLY



Install vertical slats mounting clips on the lower horizontal wire.



Insert the side and main slats vertically and assemble them in clips.



Slide the trapezoidal strip horizontally in the panel corrugation.



Mount the finishing top slat horizontally



IDEAL FOR



OTHER COLORS OF THE TAPES ARE MADE TO ORDER



TH 329 (RAL 9003)



TH 634 (RAL 3011)



TH 947 (RAL 7030)



TH 346 (RAL 9010)



TH 425 (RAL 5010)



TH 909 (RAL 7040)




TH 878 (RAL 1023)



TH 770 (RAL 8011)



TH 629 (RAL 3003)



TH 789 (RAL 8019)

- Presented here range of colors is available upon individual order, while each tape design is shown with a generally available standard color scheme.
- Colors presented in the catalog may slightly differ from the actual colors.





WE INVITE YOU TO COOPERATION!

ADDRESS:

Thermoplast Permanent Development S.A.

ul. Wilcza 3

32-590 Libiąż, Poland

SALES DEPARTMENT:

Phone: +48 32 625 86 36 **Phone:** +48 669 121 610

E-mail: sprzedaz@thermoplast.eu

OFFICE:

Phone: +48 32 627 19 82

Fax: +48 32 623 13 64

E-mail: biuro@thermoplast.eu

MADE IN

POLAND





