FENCE STRIPS cover and privacy

CATALOGUE






WE SPECIALIZE IN EXTRUSION OF PLASTIC PROFILES

- Thermoplast has over 30 years of experience in designing and building tools for extrusion, co-extrusion and post-extrusion of custom technical profiles for clients from various industries.
- We offer a wide range of standard profiles for various industries, including: furniture, refrigeration, ventilation, air-conditioning, fencing and agricultural, garden architecture, construction, sales support. We also implement individual projects, even most complex technical profiles in terms of shape, material and conditions of use.
- Thermoplast[®] is a leader among manufacturers and suppliers of original fence tapes systems on the Polish market, including fencing strips made of the highest quality polypropylene.
- We offer the widest range of original fencing strips and covers for standard 2D and 3D panels as well as fencing meshes and balcony railings on the Polish market. The offer varies both in terms of the method of mounting, structure of the strips, their width and color, which makes it possible to create functional, aesthetic, individually designed fences.

THERMOPLAST[®] KEY PRODUCT GROUPS





EXCELLENT COVER FOR YEARS

// CONTENTS

ADVANTAGES OF USING STRIPS	
HORIZONTAL MOUNTING SYSTEM 0	
APPLICATION AND BENEFITS	6
FENCE STRIPS - CLASSIC LINE	8
FENCE STRIPS - SMART MATT 0	9
FENCE STRIPS - ORANGE SKIN	
FENCE STRIPS - BASIC 1	
FENCE STRIPS - LITE TAPE	
FENCE STRIPS - LARGE TECHNORATTAN	
VERTICAL MOUNTING SYSTEM	4
FENCE STRIPS - SIMPLE LINE	4
FENCE COVERS - THE GUARD 1	6
CUSTOM MADE COLORS	9





FENCE STRIPS THERMOPLAST®

ORIGINAL FENCE COVERS

MADE IN UE

protection and privacy on properties, terraces and balconies

Thermoplast[®] fencing covers are an innovative solution that allows to create modern, aesthetic and functional fencing fillings for people who want to maintain privacy on the property, in the garden or on the balcony. They are perfect for fencing panels, mesh fencing and balustrades of balconies.

ADVANTAGES OF USING THERMOPLAST® COVERS





HORIZONTAL MOUNTING

Thermoplast® fence strips


perfect for filling panels, mesh fences and balcony railings, providing an aesthetic and durable cover. We offer them in a wide range of colors and patterns and in various widths.



VERTICAL MOUNTING

Simple Line System

a functional and aesthetic polypropylene cover for 2D and 3D fencing panels. A set consists of 60 meters of fencing tape and 100 assembly clips. We offer Simply Line in several widths, patterns and colors.



The Guard System

a set of plastic slats that is matched to 3D fence panels. The Guard is available in several sizes, so it can be used in the most popular heights of 3D panels.

THERMOPLAST® ORIGINAL FENCE COVERS ARE A GUARANTEE OF THE HIGHEST QUALITY PRODUCTS

All production processes in Thermoplast® are certified in accordance with ISO 9001, and the quality is controlled by specialists throughout production process.







IDEAL SOLUTION FOR:



PRIVATE PROPERTIES



ATES







TECHNICAL DATA

Material	Polypropylene (PP)
Darkening	≈100%
Application	fencing panels, mesh fences, balcony railings
Weight	~552 gramm/m², ~630 gramm/m², 789 gramm/m²
Assembly	assembly without the use of specialized tools
Assembly	horizontal mounting



MODERN DESIGN



AVAILABLE WIDTHS

190 mm	
1 box	26 m
1 m ²	5 lm
1 box	5 m²






MOUNTING CLIPS FOR FENCE STRIPS



UNIVERSAL CLIP AP 828

End profile with strong handle suitable for each wire thickness in a panel.

٤.



STANDARD CLIP AP 785

End profile for panels with wires with a cross-section 4 - 6 mm.



OMEGA CLI AP 888

End profile for panels with wires with a cross-section 3,5 - 5,5mm.



The use of best quality plastic - **Polypropylene**, guarantees the highest UV resistance, durability and flexibility of fencing strips.



MADE IN EU



INNOVATIVE SOLUTION



HIGHEST QUALITY



FAST AND EASY ASSEMBLY

HORIZONTAL MOUNTING

How in a quick and easy way turn a garden, terrace or balcony into a private space?



Waive the fence tape onto the panel.



Fasten the tape in the end clip.



Attach the end clip with the fence strip to the panel.

CALCULATION

FENCE						
190 m	nm		PANE	EL SIZE [M	х м]	
		2,5 X 1,2	2,5 X 1,4	2,5 X 1,6	2,5 X 1,8	2,5 X 2,0
	1	1	1	1	1	1
	2	2	2	2	2	2
	з	2	3	З	З	3
	4	3	3	4	4	4
Ϋ́	5	3	4	4	5	5
NUMBER OF PALLETS	6	4	5	5	6	6
PAI	7	5	5	6	7	7
۲a	8	5	6	7	8	8
3ER	9	6	7	8	9	9
N.	10	6	7	8	9	10
ž	15	9	11	12	14	15
	20	12	14	16	18	20
	30	18	21	24	27	30
	40	24	28	32	36	40
	50	30	35	40	45	50
		box 19	0 mm x 2	2 6 lm - [5	5 m²]	


STRIP 95 m		PANEL SIZE [M X M]							
		2,5 X 1,2	2,5 X 1,4	2,5 X 1,6	2,5 X 1,8	2,5 X 2,0			
	1	1	1	1	1	1			
	2	2	2	2	2	2			
	3	2	3	3	3	3			
	4	3	3	4	4	4			
Σ	5	3	4	4	5	5			
H	6	4	5	5	6	6			
NUMBER OF PALLETS	7	5	5	6	7	7			
Ч	8	5	6	7	8	8			
3ER	9	6	7	8	9	9			
M	10	6	7	8	9	10			
Z	15	9	11	12	14	15			
	20	12	14	16	18	20			
	30	18	21	24	27	30			
	40	24	28	32	36	40			
	50	30	35	40	45	50			
box 95 mm x 52 lm - [5 m²]									

strips 47,5 r	nm		PANE	EL SIZE [M	х м]	
		2,5 X 1,2	2,5 X 1,4	2,5 X 1,6	2,5 X 1,8	2,5 X 2,0
	1	2	2	2	2	2
	2	3	3	4	4	4
	3	4	5	5	6	6
	4	5	6	7	8	8
Σ	5	6	7	8	9	10
NUMBER OF PALLETS	6	8	9	10	11	12
PA	7	9	10	12	13	14
Ъ,	8	10	12	13	15	16
BER	9	11	13	15	17	18
MI	10	12	14	16	18	20
Z	15	18	21	24	27	30
	20	24	28	32	36	40
	30	36	42	48	54	60
	40	48	56	64	72	80
	50	60	70	80	90	100



CLASSIC LINE





CLASSIC LINE FENCE STRIP											
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	PACKAGE		INDEX					
			ROLL	26 lm	701P.XXXXK0026.190.P						
701	190 mm	1,65 mm	1,65 mm	750-770 gramm/m ²		10 x 2,55 m	701P.XXXXK2550.190.P				
701	19011111			1,05 mm	1,00 mm 200 mm		750-770 gramm7m	750 770 grammin	1,05 mm	STRIPS	10 x 2,53 m
								10 x 2, 52 m	701P.XXXXK2520.190.P		
706	95 mm	1,65 mm	750-770 gramm/m²	ROLL	2 x 26 lm	706P.XXXXK0026.95.X2					
685	47,5 mm	1,3 mm	750-770 gramm/m²	ROLL	50 lm	685P.XXXX.K0050.47.X2					

CLASSIC LINE - AVAILABLE RANGE OF COLORS




Other colors of the tapes are made to order.

Colors presented in the catalog may slightly differ from the actual colors.

Thermoplast®

SMART MATT






SMART MATT FENCE STRIP								
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	PACKAGE		INDEX		
K11	190 mm	1,1 mm	770-790 gramm/m²	ROLL	26 lm	K11.XXXXK0026.190.BL		

SMART MATT - AVAILABLE RANGE OF COLORS







TH 520 (RAL 6005)

TH 909 (RAL 7040)

TH 945 (RAL 7016) TH 900 (RAL 900)



Other colors of the tapes are made to order.






ORANGE SKIN





ORANGE SKIN FENCE STRIP									
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	PACKAGE		INDEX			
K08	190 mm	0,85 mm	580-600 gramm/m²	ROLL	26 lm	K08.XXXXK0026.190.05			
1/10	100 mm	1.20 mm	500, 600 gramm/m ²	ROLL	26 lm	K12.XXXXK0026.190.05			
K12	190 mm	1,20 mm	580-600 gramm/m ² -	STRIPS	10 x 2,55 m	K12.XXXXK2550.190.0S			

ORANGE SKIN - AVAILABLE RANGE OF COLORS



TH 520 (RAL 6005)

ļ

Other colors of the tapes are made to order.



BASIC





	BASIC FENCE STRIP									
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	PACKAGE		INDEX				
	400	190 mm 0,65 mm			ROLL	26 lm	K06.XXXXk0026.190.ST			
КОб			550 570 (²)		PE SLEEVE	50 lm	K06.XXXXK0050.190.BS			
NUO	19011111		0,0511111	0,0511111	0,0511111 550-570 grainin/1	550-570 gramm/m²	PESLEEVE	35 lm	K06.XXXXK0035.190.BS	
		-	SET	50 lm	K06.XXXXK0050.190.BS					

BASIC - AVAILABLE RANGE OF COLORS













TH 329 (RAL 9003)

TH 520 (RAL 6005)

TH 770 (RAL 8011)

TH 909 (RAL 7040)

TH 945 (RAL 7016)


TH 900 (RAL 900)



Other colors of the tapes are made to order.



LITE TAPE











BEST PRICE

RESISTANT TO WEATHER CONDITIONS RESISTANT TO RADIATION, COLOR DURABILITY

1 YEAR WARRANTY

PACKAGE

35 m of fence tape +20 end clips

LITE TAPE FENCE STRIP								
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	OPAKOWANIE		INDEX		
TCH	190 mm	0,65 mm	450 gramm/m²	ROLL	35 lm	TCH.XXXXK0035.190.KL		

LITE TAPE - AVAILABLE RANGE OF COLORS



TH 520 (RAL 6005)

TH 945 (RAL 7016)


Other colors of the tapes are made to order.

4




TECHNORATTAN LARGE





	TECHNORATTAN LARGE FENCE STRIP								
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	PACKAGE		INDEX			
				ROLL	26 lm	K20.XXXXK0026.190.RW			
К20	190 mm 2,0 mm 1210-1250 gramm/m ²	2,0 mm 1210-1250 gr	ROLL	5,1 lm	K20.XXXXK5100.190.RW				
				STRIPS	10 x 2, 55 m	K17.XXXXK2550.190.RW			

TECHNORATTAN LARGE - AVAILABLE RANGE OF COLORS





Other colors of the tapes are made to order.





SIMPLE LINE SYSTEM





1













RESISTANT TO WEATHER CONDITIONS RESISTANT TO RADIATION, COLOR DURABILITY

10 YEAR WARRANTY

TECHNICAL DATA

PACKAGE

60 m of fence tape +100 end clips

Material	Polypropylene (PP)
Darkening	≈100%
Application	2D and 3D panels
Weight	550-570 gramm/m², 580-600 gramm/m²
Assembly	assembly without the use of specialized tools
Assembly	vertical assembly

SIMPLE LINE - BASIC SYSTEM						
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	PACKAGE		INDEX
SP.K06	44 mm	0,65 mm	550-570 gramm/m²	ROLL	60 lm	SP.K06.XXXXK060.44.BS
	48 mm			ROLL	60 lm	SP.K06.XXXXK060.48.BS
	50 mm			ROLL	60 lm	SP.K06.XXXXK060.50.BS
	55 mm			ROLL	60 lm	SP.K06.XXXXK060.55.BS


SIMPLE LINE - ORANGE SKIN SYSTEM						
PROFILE NAME	WIDTH	THICKNESS	WEIGHT	PACKAGE		INDEX
SP.K08	44 mm	0,85 mm	580-600 gramm/m²	ROLL	60 lm	SP.K08.XXXXK060.44.05
	48 mm			ROLL	60 lm	SP.K08.XXXXK060.48.05
	50 mm			ROLL	60 lm	SP.K08.XXXXK060.50.0S
	55 mm			ROLL	60 lm	SP.K08.XXXXK060.55.0S







48mm [

AVAILABLE WIDTHS








50mm



155mm


FAST AND EASY ASSEMBLY



Cut the tape to appropriate length.



Fasten the tape together with a clip on the bottom wire panel.





Waive the tape vertically on the panel.




Fasten the tape together with a clip on the top panel wire










Thermoplast®

THERMOPLAST® ORIGINAL FENCE COVERS

THE GUARD SYSTEM





-



MADE IN POLAND









AFFORDABLE MADE OF FOR EVERYONE BEST QUALITY POLYVINYL CHLORIDE

E OF RESISTANT UALITY TO WEATHER CHLORIDE CONDITIONS

RESISTANT TO RADIATION, COLOR DURABILITY

10 YEAR WARRANTY

TECHNICAL DATA

		_
Material	Polyvinyl chloride (PVC)	
Darkening	≈100%]
Application	2D and 3D fence panels]
THICKNESS (main profile wall)	0,70 mm]
Assembly	assembly without the use of specialized tools]
Assembly	vertical assembly]



It is not recommended to install **TheGuard** in very windy areas (safety considerations).

THE GUARD SYSTEM						
PROFILE NAME	SLAT WIDTH	SPACING BETWEEN PANEL WIRES	MAIN PROFILE WALL THICKNESS	PACKAGE	PANEL	
	44 mm	50 mm	0,70 mm	SET	2,5 M X 1,03 M	
				SET	2,5 M X 1,23 M	
				SET	2,5 M X 1,53 M	
THE GUARD				SET	2,5 M X 1,73 M	
				SET	2,5 M X 1,93 M	
				SET	2,5 M X 2,03 M	
	48mm	55 mm	0,70 mm	SET	2,5 M X 1,03 M	
				SET	2,5 M X 1,23 M	
THE GUARD				SET	2,5 M X 1,53 M	
				SET	2,5 M X 1,73 M	
				SET	2,5 M X 1,93 M	
				SET	2,5 M X 2,03 M	




THERMOPLAST® ORIGINAL FENCE COVERS



THE SET CONSISTS OF

Each **TheGuard** set contains all necessary elements to cover 1 panel.



- main slats for vertical mounting
- 2 side slats for vertical mounting
 (2 narrower slats to be mounted at both ends of the panel)
- horizontal slat mounted in the panel corrugation
- finishing top slat
- mounting profile mounted on the lower horizontal wire

FAST AND EASY ASSEMBLY



Install mounting profiles vertical slats on the lower horizontal wire.





Slide the side and main slats vertically and place them inside the mounting profile.



HORIZONTAL SLAT

PROFILE MOUNTING

AIN SLATS

SIDE SLATS

Slide the trapezoidal strip horizontally in the panel corrugation.



Mount the finishing top slat horizontally


WARNING!

Check with the drawing, if **The Guard** system fits your fence. How to do it? It's easy!




x – maximum vertical wire height from the highest horizontal wire on the fence.

x < 33mm If dimension x is less than 33 mm, select the appropriate type of horizontal "M" slat.



Put a flat, stable surface against the horizontal bars on the back part of the fence and measure the distance "y", then compare it with the data in the table.



Measure the distance "z" and compare with notes in the table in "B" and "D" fields.

Fence measurements (distance "y")	Suggested horizontal "M" slat type	Comments
20 - 24 mm	А	
30 - 35 mm	В	For 36.7 mm width V-shape hole
36 - 41 mm	C	
30 - 35 mm	D	For 45.7 mm width V-shape hole



IDEAL FOR



OTHER COLORS OF THE TAPES ARE MADE TO ORDER



TH 329 (RAL 9003)



TH 425 (RAL 5010)




TH 346 (RAL 9010)



TH 770 (RAL 8011)



TH 878 (RAL 1023)



TH 789 (RAL 8019)



TH 629 (RAL 3003)



TH 947 (RAL 7030)



TH 634 (RAL 3011)



TH 909 (RAL 7040)

• Presented here range of colors is available upon individual order, while each tape design is shown with a generally available standard color scheme.

• Colors presented in the catalog may slightly differ from the actual colors.

TH 900 (RAL 900)





WE INVITE YOU TO COOPERATION!

ADDRESS:

Thermoplast Permanent Development S.A. ul. Wilcza 3 32-590 Libiąż, Poland

SALES DEPARTMENT:

Phone: +48 32 625 86 36 Phone: +48 660764922 E-mail: sprzedaz@thermoplast.eu

OFFICE:

Phone: +48 32 627 19 82 Fax: +48 32 623 13 64 E-mail: biuro@thermoplast.eu









www.thermoplast.eu